

Quartz Ineo First 0W-30

Engine oil

KEY DATA



INTERNATIONAL STANDARDS

- 🔹 ACEA C2
- 🔹 API SN Plus

LIGHT VEHICLE RANGE

GASOLINE & DIESEL ENGINE OIL
SAE 0W-30
ADVANCED SYNTHETIC TECHNOLOGY
LOW SAPS & FUEL ECONOMY

MANUFACTURER APPROVALS ¹

- 🔹 PSA B71 2312 & 2302
- Meets the requirements of:
- 🔹 Jaguar Land Rover STJLR.03.5007
 - 🔹 Fiat 9.55535-GS1
 - 🔹 Fiat 9.55535-DS1

Suitable for Toyota

¹ Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. Its unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

Quartz Ineo First 0W-30 is used by Stellantis (ex-PSA Group) as First fill engine oil and is recommended by PEUGEOT, CITROËN, DS, OPEL and VAUXHALL in after sales (PSA B71 2312 & 2302 specifications).

Quartz Ineo First 0W-30 is also meeting the stringent requirements of Fiat 9.55535-DS1 and Fiat 9.55535-GS1. Additionally, our engine oil is also adapted to engines requiring the Fiat 9.55535-DSX specification (as an alternative).

This pollution-control synthetic technology engine oil provides engines with the best possible protection against wear and clogging.

The post-treatment systems, sensitive to the lubricants used and expensive to maintain, are also protected over the long-term thanks to the "Low SAPS" formulation (low content of sulphated ash, phosphorus and sulphur contents).

Using this engine oil can help generate fuel savings without the need to change driving style.

Quartz Ineo First 0W-30 is particularly well-suited for use with recent engines of Stellantis/PSA, and particularly ones equipped with e-HDI using Stop & Start technologies, and hybrid engines which require new-generation engine oils.

CUSTOMERS BENEFITS

- 🔹 Reduced environmental impact: Fuel savings of 2,61% as measured by the official ACEA M111-FE test.
- 🔹 Protection for pollution-control systems: This lubricant also optimises the way in which three-way catalytic converters and particulate filters operate, preventing them from getting clogged up with soot or sludge deposits. This reduces particulate emissions, NO_x, HC and CO in particular.
- 🔹 Engine protection and cleanliness: This oil offers the best possible protection in its category against wear and clogging as soon as the engine is started up.
- 🔹 Easier cold starts: The 0W-30 grade, together with special additives, makes cold engine starts easier, even at very low temperatures (validation tests carried out down to -40C)
- 🔹 Oil change intervals: Quartz Ineo First 0W-30 retains all of its properties, in accordance with the service plans recommended by PEUGEOT, CITROËN, DS, OPEL and VAUXHALL.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	0W-30
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	50.34
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	9.9
Density at 15°C	kg/m ³	ASTM D1298	844
Viscosity index	-	ASTM D2270	187
Pour point	°C	ASTM D97	-42
OC Flash point	°C	ASTM D92	230

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubricants / Last update of this datasheet: May 23 / Quartz Ineo First 0W-30

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.